




QWATT

QW-0845 PRO DEMOLITION HAMMER



Read through carefully and understand these instructions before use.

WARNING! WHEN ELECTRIC TOOLS. ALL THE SAFETY INSTRUCTIONS SHOULD ALWAYS BE OBSERVED TO REDUCE THE RISK OF FIRE, ELECTRIC SHOCK AND PERSONAL INJURY. BEFORE ATTEMPTING TO OPERATE THE TOOL PLEASE READ ALL THE INSTRUCTIONS AND SAVE IT FOR FURTHER REFERENCE

BASIC SAFETY PRECAUTIONS FOR ALL ELECTRIC TOOLS

Keep work area clean

- Cluttered area and benches invite injuries.

Consider work area environment

- Don't use electric tools in damp or wet locations. Don't expose electric tools to rain. Keep work area well-lit, in particular. No inflammable liquids or gases must be present.

Avoid electric shock

- When you are operating tool, Don't touch metal being grounded such as pipe, Radiator freezer etc.

Keep children and visitors away

- Don't let children contact tool or extension cord. All visitors should be kept away from work place.

Store idle tool

- When not in use, tools should be stored in dry, high or locked-up place.

Don't force tool.

- It will do the job better and safer to the rate it's intended. Avoid unnecessary overload which may put the operator at risk and impair function of the tools.

- Keep away from heat, oil and sharp edges

Don't overreach

- Keep proper footing and balance at all time.

Maintain tools with care

- Keep tools sharp and clean for better and safer performance. Follow instruction for lubricating accessories. Inspect tool cords periodically and replace if damaged. Keep handles dry. Clean and free from oil and grease

Disconnect tools

- When not in use, before servicing, and when changing accessories such as blades, bits and cutters.

Remove adjusting keys and wrenches

- Form the habit of checking to see that keys and adjusting wrenches are removed from tool before turning it on.

Use extension cord

— If an extension cord is required Always check that its cross-section measurement is equal to or greater than that of the tool capabilities and so marked.

Stay alert

— Watch what you are doing. Use common sense. Do not operate tool when you are tired

Check damage parts

— Before further use of the tool. A guard or other part that is damaged should be carefully checked to determine that it will operate properly and perform its intended function Check for alignment of moving parts, binding of moving parts, breakage of moving parts, mounting and any other conditions that may affect its operation. A guard or other part that is damaged should be properly repaired or replaced by a qualified service center unless otherwise indicated elsewhere in the instruction manual. Have defective switches replaced by a qualified service center, Do not use tool if switch does not turn it on and off

Check the voltage

— Do not plug the electric tool into the mains until you have checked that the voltage shown on the data plate corresponds to the voltage available.

HOW TO OPERATE THE TOOL

After the tool is switched on, you must first wait till the disc reaches the highest speed, then begin to make grinding operation.

During the operation, don't turn "ON" or "OFF" the tool freely. Switch "ON" or "OFF" should be done after the tool is moved out of work place.

MAINTENANCE

Carbon brushes of tool must be checked regularly. when the carbon brushes are worn to 5-6mm, they must be changed in pairs. After the brushes are changed please first let the tool rotate idly for 15 minutes in order to make the brushes contact well with commutator.

The air-vent of the tool should be cleaned regularly to avoid the motor too hot due to the airvent blocked